

IN THE CLAIMS

This listing of claims replaces all prior listings:

1. (Currently Amended) An optical transceiver including:
a light emitting element for converting an electric signal into an optical signal; and
a light receiving element for converting an optical signal into an electric signal for carrying out a single-wire two-way communication by using an optical fiber;
an optical integrated chip in which said light emitting element and said light receiving element are formed on the same chip, and a light emitting section of said light emitting element and a light receiving section of said light receiving element are closely placed; and
a circuit board where a via hole for inserting said optical fiber is formed,
wherein,
said optical integrated chip is mounted on one surface of said circuit board at a position where said light emitting section and said light receiving section are fitted into said via hole,
said optical fiber is inserted into said via hole to fix from the other surface of said circuit board, and
said light emitting section and said light receiving section are placed at a distance at which a part of each section is fitted in a diameter portion of a core transversal cross-section section of said optical fiber.
2. (Original) The optical transceiver according to claim 1, wherein an electrode pad to be connected to said optical integrated chip is placed on one surface of said circuit board, and said optical integrated chip is mounted on said circuit board by flip-chip mounting.
3. (Original) The optical transceiver according to claim 1, wherein said via hole is formed by laser beam machining.
4. (Original) The optical transceiver according to claim 1, wherein a circuit for driving said optical integrated chip is formed on said circuit board.

5. (Original) The optical transceiver according to claim 1, wherein said light emitting section and said light receiving section are placed at a distance at which a part of each section is fitted in a diameter portion of a core section of said optical fiber.

6. (Currently Amended) An optical transceiver including:
a light emitting element for converting an electric signal into an optical signal;
a light receiving element for converting an optical signal into an electric signal for carrying out a single-wire two-way communication by using an optical fiber;
an optical integrated chip in which said light emitting element and said light receiving element are formed on the same chip, and a light emitting section of said light emitting element and a light receiving section of said light receiving element are ~~el~~osely placed at a distance at which a part of each section is fitted in a diameter portion of a core transversal cross-section of said optical fiber;

a circuit board where a via hole for inserting said optical fiber is formed; and
an optical component for separating an optical path from said light emitting section and an optical path to said light receiving section,
wherein,
said optical integrated chip is mounted on one surface of said circuit board at a position where said light emitting section and said light receiving section are fitted into said via hole,
said optical fiber is inserted into said via hole to fix from the other surface of said circuit board, and
said optical component is placed inside said via hole between said optical integrated chip and said optical fiber, and a first waveguide through which a transmitting light is passed and a second waveguide through which a receiving light is passed are formed between said light emitting section and said light receiving section and an end surface of said optical fiber.

7. (Original) The optical transceiver according to claim 6, wherein said optical component is a fiber in which a periphery of an inner layer section is covered by an outer layer section whose refractive index is different, and this outer layer section is covered by a total reflection film, and said first waveguide is formed such that said inner layer section is opposite to

said light emitting section, and said second waveguide is formed such that said outer layer section is opposite to said light receiving section.

8. (Original) The optical transceiver according to claim 6, wherein said optical component is a fiber covered by a total reflection film, and said first waveguide is formed such that said optical component is opposite to said light emitting section, and a total reflection film is formed on an inner surface of said via hole, and said second waveguide is formed between said via hole and said optical component.

9. (Original) The optical transceiver according to claim 6, wherein an electrode pad connected to said optical integrated chip is placed on one surface of said circuit board, and said optical integrated chip is mounted as flip-chip mounting on said circuit.

10. (Original) The optical transceiver according to claim 6, wherein said via hole is opened by laser beam machining.

11. (Original) The optical transceiver according to claim 6, wherein a circuit for driving said optical integrated chip is at least formed on said circuit board.

12. (Original) The optical transceiver according to claim 6, wherein said light emitting section and said light receiving section are placed at a distance at which at least a part of each section is fitted in a diameter portion of a core section of said optical fiber.